

PLANE NO-DROP

Version
Wall 90 cm - 800 m3/h

Collection
Design

EAN code
8034122362571



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

- Scotch brite stainless steel (AISI 304)
- Electronic control
- LED lighting
- Optional combined regenaleble Carbon.Zeo filter
- No-Drop System anti-condensation patented technology
- Emptied liquid collector

OPTIONAL ACCESSORIES

- KACL.570#I**
Extension H700 - Wall
- KACL.571#I**
Extension H960 - Wall
- KACL.815**
Protective cleaning cloths for stainless steel (box 10 pcs)
- KACL.865**
Air flow conveyer for re-circulation version (Wall)
- KACL.961**
Charcoal and Zeolite filter

TECHNICAL FEATURES


- Installation type**
Wall
- Dimensions**
90 cm
- Finishing**
Scotch brite stainless steel (AISI 304)
- Motor**
800 m³/h
- Type of control**
Electronic control
- Lighting**
LED Strip (3000K)
- Charcoal filter**
Charcoal and Zeolite filter (optional)
- Minimum distance**
Gas hob: 63 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES

- Gross weight**
30.2 kg
- Net weight**
24.9 kg
- Volumes**
0.29 m³
- Packaging size**
Length
995 mm
Height
490 mm
Depth
595 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
280 W
- Voltage**
220-240V
- Frequency**
50-60Hz
- ENERGY CLASS**
B



Falmec_Plane_No_Drop_wall


PLANE NO-DROP

Version
Wall 90 cm - 800 m3/h

Collection
Design

EAN code
8034122362571

ENERGY LABEL



PF		
S	Falmec Spa	
M	Wall 90 cm - 800 m3/h	
AEC	71,0	kWh/a
EEC	B	
FDE	26,3	
FDEC	B	
LE	16,0	
LEC	C	
GFE	70,0	
GFEC	D	
Qmin	280,0	m³/h
Qmax	480,0	m³/h
Qboost	680,0	m³/h
SPEmin	49	dBa
SPEmax	62	dBa
SPEboost	68	dBa
PO	-	W
PS	0,48	W
PI		
F	1.1	
EEL	66,2	
Qbep	382,0	m³/h
Pbep	384	Pa
Qboost	680,0	m³/h
Wbep	155,1	W
WL	12,00	W
Emiddle	192	lex
Lwa-SPEmax	62	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). PI_Additional information according to 66/2014 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.